



Lifting Electromagnet for Steel Wire Rods

HVR19 Series Room Temperature Type

Model	Cold-state Power (kw)	Cold-state Current (A)	Overall Dimension (mm)							Weight (kg)	Lifting Capacity
			A	B	C	D	E	F	G		
HVR19-14072L/1	8.6	39.1	1400	720	1180	1100	130	200	30	1760	Outer diameter of wire rod: Φ1250-Φ1350mm
HVR19-21072L/1	12.5	56.8	2100			1600			30	2670	
HVR19-27072L/1	15.6	70.9	2700			2000			40	3250	
HVR19-30072L/1	17.5	79.5	3000			2000			40	3640	Weight of wire rod: 900-1200kg/m
HVR19-34072L/1	20.3	92.3	3400			2500			40	4100	
HVR19-42072L/1	24.7	112.3	4200			3000			50	5200	
HVR19-54072L/1	31.2	141.8	5400			3500			50	6430	The length of electromagnetic lifting beam is custom-made to match the length of wire rod.
HVR19-56072L/1	33	150	5600			4000			50	6720	
HVR19-60072L/1	35	159.1	6000			4000			50	7200	
HVR19-63072L/1	36.8	167.3	6300			4000			50	7800	
HVR19-70072L/1	41.2	187.3	7000			4000			50	8400	

HVR19 Series High Temperature Type

Model	Cold-state Power (kw)	Cold-state Current (A)	Overall Dimension (mm)							Weight (kg)	Lifting Capacity
			A	B	C	D	E	F	G		
HVR19-14072L/2	7.8	35.5	1400	720	1230	1000	130	200	30	1830	Outer diameter of wire rod: Φ1250-Φ1350mm
HVR19-21072L/2	11.8	53.6	2100			1600			30	2760	
HVR19-27072L/2	14.9	67.7	2700			2000			40	3410	
HVR19-30072L/2	16.5	79.5	3000			2000			40	3790	Weight of wire rod: 900-1200kg/m
HVR19-34072L/2	19.1	75	3400			2500			40	4290	
HVR19-42072L/2	23.6	107.3	4200			3000			50	5350	
HVR19-54072L/2	29.7	135	5400			3500			50	6750	The length of electromagnetic lifting beam is custom-made to match the length of wire rod.
HVR19-56072L/2	30.9	140.5	5600			4000			50	7030	
HVR19-60072L/2	33	150	6000			4000			50	7520	
HVR19-63072L/2	35.6	161.8	6300			4000			50	8020	
HVR19-70072L/2	39.3	178.6	7000			4000			50	8650	

HVR22-54 Series

Model	Cold-state Power (kw)	Cold-state Current (A)	Overall Dimension (mm)							Weight (kg)	Lifting Capacity
			A	B	C	D	E	F	G		
HVR22-10054L/1	6.6	30	1000	540	1250	500	130	200	30	1520	Outer diameter of wire rod: Φ1250-Φ1350mm Weight of wire rod: 900-1200kg/m The length of electromagnetic lifting beam is custom-made to match the length of wire rod.
HVR22-16054L/1	10	45.5	1600		1210	600			30	2350	
HVR22-20054L/1	12.8	58.2	2000		1200	700			30	2480	
HVR22-26054L/1	15	68.2	2600		1220	800			40	3210	
HVR22-30054L/1	17.6	80	3000		1230	1000			40	3800	
HVR22-34054L/1	19	86.4	3400		1230	1200			40	4250	
HVR22-36054L/1	19.7	89.5	3600		1250	1300			40	4450	
HVR22-40054L/1	21.9	99.5	4000		1250	1550			50	5000	
HVR22-46054L/1	26.4	120	4600		1250	1800			50	5650	

Or, if you still have any queries about the specifications of lifting electromagnet for steel wire rods, please feel free to contact us.

HVR Magnetism Co., Ltd.

Tel: +86-731-28679679

Fax: +86-731-28679679

E-mail: export@hvr-magnet.com

Website: <http://www.hvr-magnet.com>

Address: 45 Zone, Liyu industrial park, Tianyuan district, Zhuzhou, Hunan Province, China